

### DISPLAY

#### AVAILABLE COLORS



Silver



Black



SHOWN IN BLACK

### KEY FEATURES

- Ultra-Bright (2500 NIT), high-heat tolerant 55-inch full HD, 1080p LED-LCD screen for improved outdoor viewing
- Portrait Orientation, use DS-5525L for landscape installation
- Direct Sunlight-Readable
- Ambient light sensor with user-selectable settings
- Anti-glare protective glass helps protect against vandalism and abuse
- Easy-to-remove front bezel and rear access panel for efficient field servicing
- Massive, water-tight side-opening cable/media bay provides easy access (Opening: 8.925" X 12.5" x 3.0" deep / Interior: 11" X 15.6" X 2.1" deep)
- Media bay power port powers media players without the need for external cords (5v@3.5amps / 12v@3amps)
- Side-mounted cable ports for improved access and visibility
- High temperature Enhanced Solar Tolerance (EST) technology prevents isotropic blackout
- Thermal-flow air ventilation system keeps the unit cool & dry in temperatures up to 122 degrees F
- Ability to operate in cold weather (-40 degrees F)
- Exterior designed to protect internal components from rain, snow, dust, insects, humidity, and salt air
- Powder-coated rust-proof aluminum exterior for strength and durability
- Quick-change filtration cartridges
- RS232 serial control with discrete on, off, and input control (located in the cable-entry compartment)
- Rear IR receiver (located in the cable-entry compartment)
- Innovative water-tight Cable Entry System seals out moisture and allows for easy hook-ups
- Weatherproof control buttons with optional tamper-proof plate
- Side control Lock-out prevents unauthorized users from changing the programming
- Includes Weatherproof Remote Control, Warranty, Manual
- Optional 20W speaker bar sold separately (Top-or-bottom mountable)

<p><b>SCREEN</b></p>	<p>SCREEN 55-inch Diagonal Color Active Matrix TFT LED</p> <p>NIT (CD/M2) 2500</p> <p>RESOLUTION 1920 x 1080 Full-HD 1080p</p> <p>ASPECT RATIO 16:9</p>	<p>CONTRAST RATIO 4000:1</p> <p>FRAME RATE 60 Hz</p> <p>VIEWING ANGLE 178° x 178°</p> <p>RESPONSE TIME 8 milliseconds</p> <p>TV FORMATS 1080p, 1080i, 720p, 720i, 480p, 480i</p>
<p><b>CONNECTIONS</b></p>	<p>RF Antenna/CATV (ATSC/QAM/NTSC) x1</p> <p>HDMI HDMI™ Input x2</p> <p>VIDEO COMPOSITE S-Video x1 and Composite Video x1, L/R Audio Inputs x1</p> <p>VIDEO COMPONENT YPbPr plus Stereo Audio x2</p> <p>PC 15-pin D-sub VGA plus Stereo Audio</p>	<p>CONTROL SET RS232 Serial, Discrete IR Control, Concealed IR Window</p> <p>AUDIO OUT SPDIF Audio(fixed), Analog 1/8" headphone jack (variable)</p> <p>SPEAKERS 20 WATT detachable speaker module(Optional)</p> <p>INPUT POWER 100-240 VAC, 50-60 Hz 2.8 A Max</p>
<p><b>TEMPERATURE TOLERANCES</b></p>	<p>OPERATING TEMP -40° to 122° F. (-40° to 50°C.)</p> <p>NON-OP. TEMP -40° to 140° F. (-40° to 60°C.)</p> <p>(OFF MODE WITH POWER APPLIED) The non-operating temperature feature requires power to be applied.</p>	
<p><b>PHYSICAL SPECS</b></p>	<p>ACCESSORIES INCLUDED Weatherproof remote control</p> <p>EXTERIOR Powder-coated aluminum</p> <p>EXTERIOR COLORS Black, &amp; Silver</p> <p>TV DIMENSIONS 29.8 W x 50.6 H x 6.9 D 757mm W x 1293mm H x 175mm D</p> <p>VESA MOUNTING PATTERN 400mm x 400mm</p>	<p>TV WEIGHT 114 lbs/51.7kg (119lbs/54kg with optional speaker)</p> <p>SHIPPING DIMENSIONS TBD</p> <p>SHIPPING WEIGHT 124 lbs/56.2kg</p> <p>RESIDENTIAL WARRANTY Two-year parts and labor</p> <p>COMMERCIAL WARRANTY Two-year parts and labor</p>